

**AMENDMENTS TO THE CLAIMS**

1. (currently amended) A method of controlling power used foref communications

5 between a mobile station and a base station, the method comprising:

determining a location of the mobile station;

based on the location, selecting aan initial power level for communication between the mobile station and the base station; and

10 starting at the initial power level, engaging in a power control process that regulates the power used fore causing communication between the mobile station and the base station at the selected power level.

2. (currently amended): The method of claim 1, wherein selecting aan initial power level for communication between the mobile station and the base station comprises:

15 referring to a database that correlates locations with initial power levels;

selecting from the database aan initial power level that is correlated with the location.

3. (currently amended): The method of claim 2, wherein engaging in a power control process that regulates the power used fore causing communication between the mobile station and

20 the base station at the select power level comprises:

sending to the mobile station an instruction to transmit at the selected initial power level,

whereby the mobile station responsively transmits at the selected initial power level.

4. (currently amended): The method of claim 2, wherein the selected initial power level is a

25 Digital Gain Unit, and wherein engaging in a power control process that regulates the power

used ~~fore~~ causing communication between the mobile station and the base station at the selected power level comprises:

translating the Digital Gain Unit into a corresponding initial base station transmit power;

and

transmitting from the base station to the mobile station at the initial base station transmit power.

5. (currently amended) The method of claim 2, wherein the selected initial power level is an initial base station transmit power level, and wherein engaging in a power control process that regulates causing communication between the mobile station and the base station at the selected power level comprises:

setting the base station to transmit at the initial base station transmit power level,

whereby the base station responsively transmits at the initial base station transmit power level.

6. (original): A base station programmed to perform the functions of claim 1.

7. (currently amended): A method of controlling power of communications between a mobile station and a base station, the method comprising:

determining a location of the mobile station;

based on the location, selecting a reverse link setpoint and an initial transmit power for the mobile station; and

using the reverse link setpoint and the initial transmit power as a basis to manage mobile station transmit power.

8. (original): The method of claim 7, wherein selecting a reverse link setpoint comprises:

referring to a database that correlates locations with reverse link setpoints; and  
selecting from the database a reverse link setpoint that is correlated with the location.

9. (currently amended): The method of claim 7, wherein using the reverse link setpoint and the initial transmit power as a basis to manage mobile station transmit power comprises:

sending to the mobile station an instruction to use the initial transmit power;  
measuring an energy level,  $E_b$ , of a signal received from the mobile station;  
based on the energy level and an estimate of air interface noise,  $N_o$ , computing a  
measured value of  $E_b/N_o$ ;

comparing the measured value of  $E_b/N_o$  with the reverse link setpoint; and

if the measured value of  $E_b/N_o$  does not match the reverse link setpoint, sending to the  
mobile station an instruction to adjust the mobile station transmit power.

10. (original): The method of claim 7, further comprising:

receiving a signal at the base station from the mobile station;

measuring a frame error rate of the signal;

comparing the measured frame error rate to a threshold frame error rate;

if the measured frame error rate does not match the threshold frame error rate, adjusting  
the reverse link setpoint;

using the adjusted reverse link setpoint as a basis to manage mobile station transmit power.

11. (original): The method of claim 10, further comprising:

- 5       based on the location, selecting a bounding value for a reverse link setpoint;  
      using the bounding value as a basis to limit the reverse link setpoint.

12. (currently amended): The method of claim 11+9, wherein selecting a bounding value for a reverse link setpoint comprises:

- 10       referring to a database that correlates locations with bounding values of reverse link setpoints; and  
      selecting from the database a reverse link setpoint that is correlated with the location.

13. (original): A base station programmed to perform the functions of claim 7.

15

14. (original): A location-based power control method for communications between a mobile station and a base station, the method comprising:

- (a) determining a location of the mobile station; and  
      (b) based on the location, selecting from a database values of initial mobile station  
20   transmit power, reverse link setpoint, and initial base station transmit power,  
      (c) instructing the mobile station to transmit at the initial mobile station transmit power;  
      (d) transmitting to the mobile station at the initial base station transmit power;

(e) performing a first process comprising (i) establishing a measured value of  $E_b/N_0$  and (ii) if the measured value of  $E_b/N_0$  does not match the reverse link setpoint, instructing the mobile station to adjust transmit power;

5 (f) performing a second process comprising (i) establishing a measured value of reverse link frame-error-rate and (ii) if the measured value of reverse link frame-error-rate does not match a threshold value of reverse link frame-error-rate, adjusting the reverse link setpoint; and

(g) performing a third process comprising (i) receiving a measured value of forward link frame-error-rate and (ii) if the received value of forward link frame-error-rate does not match a threshold value of forward link frame-error-rate, adjusting the forward link transmit power.

10

15. (original): A base station programmed to perform the functions of claim 14.

16. (original): A method of controlling power of communications between a mobile station and a base station, the method comprising the following steps:

15

(a) determining a location of the mobile station;

(b) based on the location, selecting a setpoint and a mobile station transmit power;

(c) instructing the mobile station to transmit at the mobile station transmit power;

(d) computing an energy-to-noise measure for a signal received from the mobile station;

(e) determining if the energy-to-noise measure matches the setpoint; and

20

(f) in response to a determination that the energy-to-noise measure does not match the initial setpoint, instructing the mobile station to adjust the mobile station transmit power.

17. (original): The method of claim 16, further comprising:

(g) monitoring an error rate of signals received from the mobile station;  
(h) determining if the error rate matches a predetermined threshold;  
(i) in response to a determination that the error rate does not match the predetermined threshold, adjusting the setpoint.

5

18. (original): The method of claim 17, further comprising:  
periodically repeating steps (d)-(f) and (g)-(i).

19. (original): The method of claim 18 further comprising:

10 detecting a new location of the mobile station; and  
repeating steps (b)-(f) based on the new location.

20. (original): A base station programmed to perform the functions of claim 16.

15 21. (original): A method of controlling power of communications between a mobile station and a  
base station, the method comprising the following steps:

determining a location of the mobile station;  
based on the location, selecting a base station transmit power level;  
transmitting from the base station at the base station transmit power level;  
20 monitoring an error rate of signals received by the mobile station;  
determining if the error rate matches a predetermined threshold;  
in response to a determination that the error rate does not match the predetermined  
threshold, adjusting the base station transmit power level.

22. (original): The method of claim 21, wherein selecting a base station transmit power level comprises selecting a Digital Gain Unit and translating the Digital Gain Unit into a base station transmit power level.

5

23. (currently amended): A power control system comprising:

means for determining a location of ~~at~~ the mobile station;

means for selecting ~~an~~ initial power level for communication between the mobile station and the base station, based on the location; and

10

means for engaging in a power control process, starting at the initial power level, that regulates the power used for ~~causing~~ communication between the mobile station and the base station at the selected power level.